



SR NO	FEATURES	SR NO	FEATURES
1	EMERGENCY STOP At Both Ground Control And Platform Control	11	USER FRIENDLY And Intuitive Controls
2	Stable STEEL STRUCTURE Base	12	HILL HOLD Rear Wheel Brakes
3	Collapsible Guard Rail Mechanism With FULL HEIGHT Swing Gate	13	MILITARY SPEC QR Connectors
4	CHECKERED Steel Plate On Platform For Better Grip	14	Maximum Height AUTO CUT-OFF Function
5	POTHOLE GUARDS For Added Safety	15	Multiple SAFETY HARNESS Anchor Points
6	PROPORTIONAL Control For Lift And Drive	16	Dual Fuse Setup For Superior OVERLOAD PROTECTION
7	SOLID Rubber Non-marking Tyres	17	EASY SERVICEABLE Hydraulic Cylinder Design
8	DUAL Front Wheel Drive	18	SWING-OUT Component And Battery Trays For Easy SERVICEABILITY
9	VOLT METER,HOUR METER And HAZARD LIGHT	19	Platform Control with DIAGNOSTIC DISPLAY
10	Emergency Descent Valve In ERGONOMIC Location		

Specifications





MODELS		SCL-2646		SCL-3246		SCL-4046	
MEASUREMENTS	ММ	FT & INCH	ММ	FT & INCH	MM	FT & INCH	
WORKING HEIGHT	9754	32 ft	11583	38 ft	14021	46 ft	
PLATFORM HEIGHT	7925	26 ft	9754	32 ft	12192	40 ft	
A PLATFORM HEIGHT STOWED		3 ft 9 in	1270	4 ft 2 in	1397	4 ft 7 in	
B PLATFORM LENGTH : OUTSIDE EXTENDED	2235 3150	7 ft 4 in 10 ft 4 in	2235 3150	7 ft 4 in 10 ft 4 in	2235 3150	7 ft 4 in 10 ft 4 in	
© SLIDE-OUT PLATFORM EXTENSION DECK	915	3 ft	915	3 ft	915	3 ft	
D PLATFORM WIDTH : OUTSIDE GUARDRAIL HEIGHT TOEBOARD HEIGHT	1093 1042 153	3 ft 7 in 3 ft 5 in 6 in	1093 1042 153	3 ft 7 in 3 ft 5 in 6 in	1093 1042 153	3 ft 7 in 3 ft 5 in 6 in	
E HEIGHT-STOWED: FOLDING GUARDRAILS RAILS FOLDED	2304 1600	7 ft 7 in 5 ft 3 in	2413 1753	7 ft 10 in 5 ft 9 in	2540 1880	8 ft 4 in 6 ft 2 in	
EXTENDED	2413 3327	7 ft 11 in 10 ft 11 in	2413 3327	7 ft 11 in 10 ft 11 in	2413 3327	7 ft 11 in 10 ft 11 in	
G WIDTH		3 ft 11 in	1194	3 ft 11 in	1194	3 ft 11 in	
H WHEEL BASE		6 ft 1 in	1854	6 ft 1 in	1854	6 ft 1 in	
GROUND CLEARANCE - CENTER WITH POTHOLE GUARD DEPLOYED	89 19	3.5 in 0.75 in	89 19	3.5 in 0.75 in	89 19	3.5 in 0.75 in	



